

Numero de parte 390700 VALVULA PARKER EUROPEA:



DESCRIPTION	VALUE
PRODUCT TYPE	FLUID CONTROL VALVE SOLENOID
CONFIGURATION/TYPE	2-WAY
OPERATION	NORMALLY CLOSE
MEDIA	INERT GASES, LIGHT OIL
PIPE/PORT SIZE	1/4"
MAX OPERATING PRESSURE DIFF	0-2 Bar
ENCLOSURE	N/A
VOLTAGE/FREQUENCY RATING	115V/60Hz
ORIFICE DIAMETER	4mm
POWER CONSUMPTION	N/A
CONNECTION	Rp
COIL INSULATION	IP65
COIL TERMINATIONS	DIN
BODY MATERIAL	BRASS
MIN OPERATING PRESSURE DIFF	0

COIL TERMINATIONS	DIN
BODY MATERIAL	BRASS
MIN OPERATING PRESSURE DIFF	0
FLOW COEFFICIENT/RATING	0.318
STANDARDS	N/A
AMBIENT TEMPERATURE	+50°C (F) ; +80°C (H)
FLUID TEMPERATURE	-10°C +140°C
SEALS	FKM
ADDITIONAL DETAIL	Recommended coil(s): KT09-KT10-KH09
TRADE/BRAND NAME	N/A
SYNONYM	N/A
MOPD OIL	N/A
MOPD WATER	N/A
MOPD STEAM	N/A
MOPD AIR/GAS	N/A
ACTUATION	N/A
DESIGN	N/A
CONFIGURATOR	NO
CAD DRAWING AVAILABLE	YES