

Industrial Hose, Valves & Process Equipment



2 Way Normally Closed Direct Lift Valve



Brass Body Material

- Applications:**
- Material transfer
 - Molding
 - Vending machines
 - Instrumentation
 - Welding equipment
 - Water treatment systems
 - Spray equipment
 - Dental equipment
 - Laundry equipment
 - Food processing machinery

- Compliances:**
- UL® and CSA approvals are generally available on valves with applicable coil/enclosure combinations

- Caution:**
- Use of nonlubricated gaseous media will substantially limit valve life
 - Pressure ratings may vary when valve is used with DC voltage supply

Solenoid Enclosure: NEMA 4, 4X
Voltage Rating: 110 VAC, 50 Hz, 120 VAC, 60 Hz

Pipe Size NPT (in)	Orifice Size (in)	Cv Flow	Operating Pressure Differential (psi)	Watt Rating (W)	Seal Material	Coil Type	AC Voltage		
							Order No.	Model No.	Net Price
3/8	5/8	3.0	0 to 150	11	Buna-N	Gold Ring Valve	MA0093606	06F23C2140ACF4C05	\$103.02
1/2	5/8	4.0	0 to 100	10	Buna-N	Skinner Valve	MA1870702	72218BN4UNOONOC111P3	114.35
			0 to 150	11	Buna-N	Gold Ring Valve	MA4222684	08F23C2140ACF4C05	103.02
3/4	19/32	5.5	0 to 230	10	Buna-N	Skinner Valve	MA1870714	7221GBN51N00NOC111P3	118.60
	3/4	5.0	0 to 150	11	Buna-N	Gold Ring Valve	MA2093426	12F23C2148ACF4C05	113.02



2 Way Normally Closed Pilot Operated Valve



Brass Body Material

- Applications:**
- Automated systems
 - Dispensing systems
 - Instrumentation
 - Welding equipment
 - Restaurant equipment
 - Food processing machinery
 - Water treatment systems
 - Laundry equipment

- Compliances:**
- UL® and CSA approvals are generally available on valves with applicable coil/enclosure combinations


- Caution:**
- Use of nonlubricated gaseous media will substantially limit valve life
 - Pressure ratings may vary when valve is used with DC voltage supply

Solenoid Enclosure: NEMA 4, 4X
Voltage Rating: 110 VAC, 50 Hz, 120 VAC, 60 Hz

Pipe Size NPT (in)	Orifice Size (in)	Cv Flow	Max. Operating Pressure Differential (psi)	Max. Air/Inert Gas Pressure Differential (psi)	Max. Water Pressure Differential (psi)	Max. Light Oil Pressure Differential (psi)	Watt Rating (W)	Seal Material	Coil Type	AC Voltage		
										Order No.	Model No.	Net Price
1/4	11/32	1.2	300	300	300	300	6	Buna-N	Gold Ring Valve	MA5619183	04F25C2122CAF4C05	\$72.34
3/8	5/8	3.0	200	200	135	135	6	Buna-N	Gold Ring Valve	MA3517127	06F22C2140AAF4C05	88.30
1/2	1/2	2.8	300	300	300	300	10	Buna-N	Skinner Valve	MA1870637	73212BN4TN00NOC111P3	152.26
	5/8	4.0	200	200	135	135	6	Buna-N	Gold Ring Valve	MA5621746	08F22C2140AAF4C05	89.87
3/4	3/4	5.0	125	125	125	125	6	Buna-N	Gold Ring Valve	MA9790980	12F22C2148AAF4C05	107.53
			150	150	150	150	10	Buna-N	Skinner Valve	MA1870707	73218BN5VN00NOC111P3	114.54
		7.3	300	300	300	300	10	Buna-N	Skinner Valve	MA1870638	73212BN52N00NOC111P3	191.95
1	1	11.0	300	300	300	300	10	Buna-N	Skinner Valve	MA1870639	73212BN63N00NOC111P3	252.60
		12.5	230	230	230	230	10	Buna-N	Skinner Valve	MA1870718	7321GBN64N00NOC111P3	188.69
2	1 9/16	38.6	230	230	230	230	10	Buna-N	Skinner Valve	MA1870719	7321GBN99N00NOC111P3	434.24



2 Way Normally Open Direct Lift & Pilot Operated Valve



Brass Body Material

- Applications:**
- Automated systems
 - Dispensing systems
 - Instrumentation
 - Welding equipment
 - Restaurant equipment
 - Food processing machinery
 - Water treatment systems
 - Laundry equipment

- Compliances:**
- UL® and CSA approvals are generally available on valves with applicable coil/enclosure combinations

- Caution:**
- Use of nonlubricated gaseous media will substantially limit valve life
 - Pressure ratings may vary when valve is used with DC voltage supply

Solenoid Enclosure: NEMA 4, 4X
Voltage Rating: 110 VAC, 50 Hz, 120 VAC, 60 Hz

Pipe Size NPT (in)	Orifice Size (in)	Cv Flow	Operating Pressure Differential (psi)	Max. Air/Inert Gas Pressure Differential (psi)	Max. Water Pressure Differential (psi)	Max. Light Oil Pressure Differential (psi)	Watt Rating (W)	Seal Material	Coil Type	AC Voltage		
										Order No.	Mfr. No.	Net Price
3/8	5/8	3.0	0 to 150	150	150	150	11	Buna-N	Gold Ring Valve	MA5621407	06F23O2140ACF4C05	\$172.97
1/2	5/8	4.0	0 to 150	150	150	150	11	Buna-N	Gold Ring Valve	MA5626058	08F23O2140ACF4C05	172.97
3/4	3/4	5.5	0 to 150	150	150	150	11	Buna-N	Gold Ring Valve	MA1870626	12F23O2148ACF4C05	182.75
1	1	13.0	5 to 125	125	125	125	11	Buna-N	Gold Ring Valve	MA5622860	16F24O2164ACF4C05	253.56
1 1/2	1 1/4	22.5	5 to 125	125	125	125	11	Buna-N	Gold Ring Valve	MA1870629	24F24O2180ACF4C05	395.73

